

6-EVF-40 (12V40AH/10HR)

LONG WAY 6-EVF-40 is one of the Deep Cycle battery of LONGWAY BATTERY.

This series adopts AGM technology, which has high safety & reliability, maintenance-free, high charging rate, low self-discharge, and long life.

Applications: Electric vehicles, Electric scooter, Electric wheel chair, Electric play car for children Sanitation vehicles and police patrol car etc.



Specifications: Designed according with the IEC60254-2014

12Volts (6 Cells per unit) Nominal Voltage

Nominal Capacity @25°C

20hr -rate (2.00A) 44.2Ah @ 1.75V per cell@25°C (77°F) 40.0AH @ 1.75V per cell@25°C (77°F) 10Hr-rate (4.00A) 5Hr-rate (6.80A) 36.8AH@1.70Vper cell@25°C (77°F) 34.7AH@1.70Vper cell@25℃ (77°F) 3Hr-rate (10.0A)

Weight Approx.13.0 \pm 3%kg(28.65lbs) Internal Resistance

Approx. 8.4mΩ full charged @25°C

Maximum Discharge Current 400A(3sec)

Discharge: -20 ℃~50 ℃; Charge: 0 ℃~40 ℃ Operating Temperature Range

Storage: -20 ℃~40 ℃

Equalization and Cycle Service 14.40~15.0VDC/unit Average @ 25°C

Maximum Charging Current 10.0A

Terminal I4 (M6 stem)

Container Material

ABS (UL 94-HB) & Flame Retardant (94-V0)

available upon request

Self Discharge LONGWAY batteries can be stored for more than 6

months and the Self-discharge ratio less than 3%per month at 25℃.Please charge batteries before using.

ISO9001:2015 ISO14001:2015 ISO45001:2018 ISO50001:2011

APPLICATION STANDARDS

- ISO 7176-25 2013
- IEC 60254-1- 2005
- SAE J1495-2018
- UL1989 (MH46789)

Dimensions

Length:196 \pm 2mm Width:166±2mm Height: 175±2mm

Total Height: 175±2mm


196

Outer Dimensions







Terminal Type



Cycle Service Life



Capacity Retention Characteristic



Kaiying Power Supply & Electrical Equip Co., Ltd

Add: Laogang Industrial Area, Chengxiang Town , Anxi, Quanzhou City, Fujian Province , China

Tel: 0595-68782266 Fax: 0595-68782222 Web: www.longwaybattery.com Email: sales@longwaybattery.com KY-IOP-6-EVF-40 A1. May