

6-FVF-45 (12V45AH/10HR)

0-EVF-45 (12V45AA) 10AK)		600 000
LONG WAY 6-EVF-45 is one of the Deep Cycle battery of LONGWAY BATTERY.		
This series adopts AGM technology, which has high safety & reliability,		
maintenance-free, high charging rate, low self-discharge, and long life.		Concentry
Applications: Electric vehicles, Electric scooter, Electric wheel chair, Electric play car		
for children Sanitation vehicles ar	nd police patrol car etc.	See Ce of Pb
Specifications: Designed accor	ding with the IEC60254-2014	
Nominal Voltage	12Volts (6 Cells per unit)	THE WAY
Nominal Capacity	@25°C (77°F)	177 Da 184
20hr -rate (2.25A)	50.0Ah @1.75V per cell@25℃	
10Hr-rate (4.50A)	45.0AH @1.75V per cell@25℃	CEPTIFICATO
5Hr-rate (7.65A)	42.0AH @1.70Vper cell@25℃	ISO9001:2015
3Hr-rate (11.2A)	35.0AH @1.70Vper cell@25℃	ISO14001:2015
Weight	Approx.14.2 ± 3%kg(35.27lbs)	ISO45001:2018
Internal Resistance Maximum Discharge Current	Approx. 6.50mΩ full charged @25℃ 400A(3sec)	ISO50001:2011
Operating Temperature Range	HubA(sec) Discharge: -20℃~50℃; Charge: 0℃~40℃ Storage: -20℃~40℃	APPLICATION STANDARDS
Equalization and Cycle Service Maximum Charging Current	14.40~15.0VDC/unit Average @ 25℃ 11.50A	• ISO 7176-25 - 2013
Terminal	I4 (M6 stem)	IEC 60254-1- 2005

ABS (UL 94-HB) & Flame Retardant (94-V0)

LONGWAY batteries can be stored for more than 6 months and the Self-discharge ratio less than 3%per

month at 25°C.Please charge batteries before using.

available upon request

196

000

0

000

99

Outer Dimensions

O


Self Discharge


Container Material

Dimensions


Length:196±2mm Width :166±2mm Height :175±2mm Total Height :175±2mm

Cycle Service Life





Capacity Retention Characteristic



Kaiying Power Supply & Electrical Equip Co., Ltd

Add: Laogang Industrial Area, Chengxiang Town , Anxi, Quanzhou City, Fujian Province , China

Tel: 0595-68782266 Fax: 0595-68782222 Web: www.longwaybattery.com Email: sales@longwaybattery.com KY-IOP-6-EVF-45 A1. May 2022

NOTE: This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact Long Way for the latest information.

- IEC 60254-1- 2005
- SAE J1495-2018
- UL1989 (MH46789)

Ø15 **Ø**6

T4

Terminal Type