



Sound/Speaker System Battery

6FM4.5 (12V4.5Ah)

LONGWAY speaker batteries are designed and developed according to the characteristics of instant large current, deep discharge, easy over-discharge and high-frequency vibration required in the use of speaker. The product has the advantages of long cycle life, good performance of large current discharge, low self-discharge rate, strong recovery ability of over-discharge, strong anti-vibration ability, etc., which can meet the special performance requirements of speaker batteries. Products pass UL, CE, RoHS certification, and can be shipped by sea or air.



General Feature

- High reliability, safe without leakage, can be used in any position
- Excellent recovery performance after deep discharge
- Environmentally friendly products
Meet EU battery directive RoHS and REACH standards
- Maintenance free
- Widely applicable temperature range, can be used at -20°C~60°C
- Low self-discharge rate. The average monthly self-discharge rate of the battery is less than 2.5%
(It is recommended to recharge after storage for 6 months or before use)


Applications

- Outdoor battery speaker
- Portable video speaker
- Outdoor song on-demand stereo
- Wireless Bluetooth speaker
- Wireless line array speaker
- Square dance speaker
- And company meeting, wedding hosting, outdoor activities and other audio

Performance

| | |
|-----------------------------|---|
| Nominal Voltage | 12V (6cell) |
| Capacity | @25°C |
| 20hr Rate (0.22A) | 5.18Ah @ to 1.75V/cell |
| 3hr Rate (1.22A) | 3.67Ah @ to 1.70V/cell |
| 27min Rate (4.50A) | 2.63Ah @ to 1.60V/cell |
| Weight | Approx (1.43 ± 3%)kg (3.15lbs) |
| Internal Resistance | Approx 29.0mΩ fully charged @25°C |
| Maximum Discharge Current | 55A(3sec) |
| Terminal | F1 |
| Operating Temperature Range | Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C |
| Container Material | ABS(UL94 HB)/UL94-V0 Optional |

Dimensions



| | | |
|--------------|---------|----------|
| Length | 90.0mm | 3.54inch |
| Width | 70.0mm | 2.76inch |
| Height | 102.0mm | 4.02inch |
| Total height | 107.0mm | 4.21inch |

Battery use

Cycle use

- 1.Limit the initial charging current to no more than 1.35A
- 2.Keep charging voltage at 14.40-15.00V/unit, and continue charging at least 3 hours after the charging current reduces to 0.09A to ensure full charge
- 3.The compensation coefficient of charging voltage and temperature is -5mv/cell / °C

Float use

- 1.Limit the initial charging current to no more than 1.35A
2. Keep charging voltage at 13.50-13.80V/unit. When the voltage reaches the constant voltage the current gradually decreases until the battery is fully charged and continues to charge
- 3.The compensation coefficient of charging voltage and temperature is -3mv/cell / °C



Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
KY-IOP-LW12-4.5 B0.May 2023


Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery, Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information




Sound/Speaker System Battery

6FM4.5 (12V4.5Ah)


Floating Charging Life VS Temperature




Floating Charging Characteristics Diagram




Cycle Life




Cycle charging characteristic diagram



Temperature and capacity characteristics



Self-discharge characteristic



Constant current characteristics(A,25°C)

| F.V/TIME | 5min | 10min | 15min | 30min | 60min | 90min | 2h | 3h | 5h | 10h | 20h |
|----------|------|-------|-------|-------|-------|-------|------|------|------|------|------|
| 9.6 | 15.1 | 9.90 | 8.80 | 4.90 | 2.93 | 2.09 | 1.64 | 1.23 | 0.82 | 0.47 | 0.25 |
| 9.9 | 14.6 | 9.60 | 8.54 | 4.75 | 2.84 | 2.05 | 1.63 | 1.22 | 0.81 | 0.47 | 0.25 |
| 10.2 | 14.3 | 9.41 | 8.45 | 4.70 | 2.81 | 2.01 | 1.62 | 1.22 | 0.81 | 0.47 | 0.25 |
| 10.5 | 13.9 | 9.11 | 8.10 | 4.51 | 2.69 | 1.97 | 1.60 | 1.20 | 0.80 | 0.46 | 0.25 |
| 10.8 | 13.5 | 8.84 | 8.03 | 4.47 | 2.67 | 1.93 | 1.59 | 1.19 | 0.79 | 0.46 | 0.25 |

Constant power discharge characteristic (W,25°C)

| F.V/TIME | 5min | 10min | 15min | 30min | 60min | 90min | 2h | 3h | 5h | 10h | 20h |
|----------|------|-------|-------|-------|-------|-------|------|------|------|------|------|
| 9.6 | 168 | 112 | 100 | 56.2 | 33.9 | 24.5 | 19.2 | 14.7 | 9.80 | 5.65 | 3.01 |
| 9.9 | 163 | 108 | 97.3 | 54.5 | 32.9 | 24.0 | 19.0 | 14.5 | 9.70 | 5.62 | 3.00 |
| 10.2 | 160 | 106 | 96.3 | 53.9 | 32.5 | 23.5 | 19.0 | 14.4 | 9.70 | 5.60 | 2.99 |
| 10.5 | 155 | 103 | 92.3 | 51.7 | 31.2 | 23.0 | 18.8 | 14.3 | 9.60 | 5.57 | 2.98 |
| 10.8 | 150 | 100 | 91.5 | 51.2 | 30.9 | 22.5 | 18.6 | 14.1 | 9.50 | 5.56 | 2.97 |



Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
 Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
 Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
 KY-IOP-LW12-4.5 B0.May 2023

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery, Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information