



Sound/Speaker System Battery

6FM35G (12V35Ah)

LONGWAY speaker batteries are designed and developed according to the characteristics of instant large current, deep discharge, easy over-discharge and high-frequency vibration required in the use of speaker. The product has the advantages of long cycle life, good performance of large current discharge, low self-discharge rate, strong recovery ability of over-discharge, strong anti-vibration ability, etc., which can meet the special performance requirements of speaker batteries. Products pass UL, CE, RoHS certification, and can be shipped by sea or air.



General Feature

- High reliability, safe without leakage, can be used in any position
- Excellent recovery performance after deep discharge
- Environmentally friendly products
Meet EU battery directive RoHS and REACH standards
- Maintenance free
- Widely applicable temperature range, can be used at -20°C~60°C
- Low self-discharge rate. The average monthly self-discharge rate of the battery is less than 2.5%
(It is recommended to recharge after storage for 6 months or before use)


Applications

- Outdoor battery speaker
- Portable video speaker
- Outdoor song on-demand stereo
- Wireless Bluetooth speaker
- Wireless line array speaker
- Square dance speaker
- And company meeting, wedding hosting, outdoor activities and other audio

Performance

Nominal Voltage	12V (6cell)
Capacity	@25°C
20hr Rate (3.50A)	35.0Ah @ to 1.75V/cell
5hr Rate (5.95A)	29.7Ah @ to 1.70V/cell
3hr Rate (8.75A)	26.2Ah @ to 1.60V/cell
Weight	Approx (10.3 ± 3%)kg (22.71lbs)
Internal Resistance	Approx 8.00mΩ fully charged @25°C
Maximum Discharge Current	175A(3sec)
Terminal	F10
Operating Temperature Range	Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C
Container Material	ABS(UL94 HB)/UL94-V0 Optional

Dimensions



	mm	inch
Length	195mm	7.68inch
Width	130mm	5.12inch
Height	161mm	6.34inch
Total height	180mm	7.09inch

Battery use

Cycle use

1. Limit the initial charging current to no more than 8.75A
2. Keep charging voltage at 14.40-15.00 V/unit, and continue charging at least 3 hours after the charging current reduces to 0.70A to ensure full charge
3. The compensation coefficient of charging voltage and temperature is -5mv/cell /°C

Float use

1. Limit the initial charging current to no more than 8.75A
2. Keep charging voltage at 13.50-13.80 V/unit. When the voltage reaches the constant voltage the current gradually decreases until the battery is fully charged and continues to charge
3. The compensation coefficient of charging voltage and temperature is -3mv/cell /°C



Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
KY-IOP-LW12-35B B0.May 2023


Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery, Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information




Sound/Speaker System Battery

6FM35G (12V35Ah)


Floating Charging Life VS Temperature




Floating Charging Characteristics Diagram




Cycle Life




Cycle charging characteristic diagram



Temperature and capacity characteristics



Self-discharge characteristic



Constant current characteristics(A,25°C)

F.V/TIME	5min	10min	15min	30min	60min	90min	2h	3h	5h	10h	20h
9.60	94.5	80.5	61.3	36.1	19.6	12.1	8.88	6.11	4.09	3.55	1.83
9.90	91.7	78.1	60.0	35.3	19.2	12.0	8.84	6.08	4.07	3.54	1.82
10.2	89.8	76.5	58.8	34.6	18.8	11.9	8.75	6.02	4.05	3.52	1.81
10.5	84.6	74.1	57.0	33.5	18.2	11.8	8.66	5.96	4.04	3.51	1.81
10.8	77.5	71.9	55.9	32.9	17.9	11.7	8.58	5.90	4.03	3.50	1.80

Constant power discharge characteristic (W,25°C)

F.V/TIME	5min	10min	15min	30min	60min	90min	2h	3h	5h	10h	20h
9.60	1021	879	698	404	223	140	104.4	72.2	49.0	42.4	22.0
9.90	990	853	659	396	219	139	103.9	71.9	48.8	42.2	21.8
10.2	970	835	646	388	215	138	102.9	71.2	48.6	42.0	21.8
10.5	913	809	625	376	208	136	101.9	70.4	48.4	41.9	21.7
10.8	837	785	613	369	204	135	100.8	69.7	48.3	41.8	21.6



Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
 Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
 Add: Kaiying IndustrialArea, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
 KY-IOP-LW12-35B B0.May 2023

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery, Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information