



General VRLA Battery

4FM200G (8V200Ah)

The LONGWAY General Series middle batteries (more than 24Ah) are designed and developed using AGM technology and valve controlled sealing technology. They can meet conventional performance requirements, with a designed float charging life of over 8 years. The valve controlled non-spillable structure design allows safe use in any direction and is certified by sea and air freight. The battery performance also meets international standards. such as IEC60896-2012, UL1989.etc.



General Feature	Applications
<ul style="list-style-type: none"> High reliability, safe without leakage, can be used in any position Excellent recovery performance after deep discharge Environmentally friendly products. Meet EU battery directive RoHS and REACH standards Maintenance free Widely applicable temperature range, can be used at -20 °C~60°C Low self-discharge rate. The average monthly self-discharge rate of the battery is less than 2.5% (It is recommended to recharge after storage for 6 months or before use) 	<ul style="list-style-type: none"> Emergency lights; Alarm system Electrical test equipment; communication Equipment Uninterruptible power supply; Fire & Security Electric toys; Control instruments Portable Movie & Video lights Electric tools; Solar system Robots and control machines and other

Performance	Dimensions																																		
<table border="1"> <tr> <td>Nominal Voltage</td> <td>8V (4cells)</td> </tr> <tr> <td>Capacity</td> <td>@25°C</td> </tr> <tr> <td>10hr Rate (20.0A)</td> <td>200 Ah @ to 1.75V/cell</td> </tr> <tr> <td>5hr Rate (34.0A)</td> <td>170 Ah @ to 1.70V/cell</td> </tr> <tr> <td>3hr Rate (50.0 A)</td> <td>150 Ah @ to 1.60V/cell</td> </tr> <tr> <td>Weight</td> <td>Approx (35.5±3%)kg (78.26lbs)</td> </tr> <tr> <td>Internal Resistance</td> <td>Approx 2.30mΩ fully charged @25°C</td> </tr> <tr> <td>Maximum Discharge Current</td> <td>400A(3sec)</td> </tr> <tr> <td>Terminal</td> <td>I7-1</td> </tr> <tr> <td>Operating Temperature Range</td> <td>Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C</td> </tr> <tr> <td>Container Material</td> <td>ABS(UL94 HB)/UL94-V0 Optional</td> </tr> </table>	Nominal Voltage	8V (4cells)	Capacity	@25°C	10hr Rate (20.0A)	200 Ah @ to 1.75V/cell	5hr Rate (34.0A)	170 Ah @ to 1.70V/cell	3hr Rate (50.0 A)	150 Ah @ to 1.60V/cell	Weight	Approx (35.5±3%)kg (78.26lbs)	Internal Resistance	Approx 2.30mΩ fully charged @25°C	Maximum Discharge Current	400A(3sec)	Terminal	I7-1	Operating Temperature Range	Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C	Container Material	ABS(UL94 HB)/UL94-V0 Optional	<table border="1"> <tr> <td>Length</td> <td>260mm</td> <td>10.24inch</td> </tr> <tr> <td>Width</td> <td>180mm</td> <td>7.09inch</td> </tr> <tr> <td>Height</td> <td>280mm</td> <td>11.02inch</td> </tr> <tr> <td>Total height</td> <td>280mm</td> <td>11.02inch</td> </tr> </table>	Length	260mm	10.24inch	Width	180mm	7.09inch	Height	280mm	11.02inch	Total height	280mm	11.02inch
Nominal Voltage	8V (4cells)																																		
Capacity	@25°C																																		
10hr Rate (20.0A)	200 Ah @ to 1.75V/cell																																		
5hr Rate (34.0A)	170 Ah @ to 1.70V/cell																																		
3hr Rate (50.0 A)	150 Ah @ to 1.60V/cell																																		
Weight	Approx (35.5±3%)kg (78.26lbs)																																		
Internal Resistance	Approx 2.30mΩ fully charged @25°C																																		
Maximum Discharge Current	400A(3sec)																																		
Terminal	I7-1																																		
Operating Temperature Range	Discharge:-20°C~60°C; Charge:0°C~50°C Storage:-20°C~40°C																																		
Container Material	ABS(UL94 HB)/UL94-V0 Optional																																		
Length	260mm	10.24inch																																	
Width	180mm	7.09inch																																	
Height	280mm	11.02inch																																	
Total height	280mm	11.02inch																																	

Battery use
Cycle use <ol style="list-style-type: none"> Limit the initial charging current to no more than 50A Keep charging voltage at 9.6-10.0V/unit.and continue charging at least 3 hours after the charging current reduces to 4.0A to ensure full charge The compensation coefficient of charging voltage and temperature is -5mv/cell/°C
Float use <ol style="list-style-type: none"> Limit the initial charging current to no more than 50A Keep charging voltage at 9.0-9.2V/unit.When the voltage reaches the constant voltage,the current gradually decreases until the battery is fully charged and continues to charge The compensation coefficient of charging voltage and temperature is -3mv/cell/°C


			Kaiying Power Supply & Electrical Equip Co., Ltd Tel:0595-68782266 Fax:0595-68782222 Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China KY-IOP-LW8-200U B0. May 2023	Email: sales@longwaybattery.com Website: http://www.longwaybattery.com
--	--	--	--	---

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery. Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information.



General VRLA Battery 4FM200G (8V200Ah)


Floating Charging Life VS Temperature



Floating Charging Characteristics Diagram



Cycle Life



Cycle charging characteristic diagram



Temperature and capacity characteristics



Self-discharge characteristic



Constant current characteristics(A,25°C)

F.V/TIME	5min	10min	15min	30min	60min	90min	2h	3h	5h	10h	20h
6.40	550.0	460.0	350.0	206.0	112.0	73.1	52.8	35.5	22.3	20.3	11.2
6.60	533.5	446.2	339.5	199.8	108.6	72.4	52.3	35.2	22.2	20.2	11.1
6.80	522.5	437.0	336.0	197.8	107.5	72.0	52.0	35.0	22.1	20.1	11.1
7.00	506.0	423.2	322.0	189.5	103.0	71.3	51.5	34.7	22.0	20.0	11.0
7.20	491.2	410.8	319.2	187.9	102.1	70.6	51.0	34.3	22.0	20.0	11.0

Constant power discharge characteristic (W,25°C)

F.V/TIME	5min	10min	15min	30min	60min	90min	2h	3h	5h	10h	20h
6.40	3069	2594	1995	1180	648	427.5	313.5	212.1	134.0	121.8	67.0
6.60	2977	2517	1935	1145	629	423.3	310.4	210.0	133.3	121.2	66.7
6.80	2916	2465	1915	1133	623	421.2	308.9	209.0	132.8	120.7	66.4
7.00	2823	2387	1835	1086	597	417.0	305.8	206.9	132.3	120.2	66.1
7.20	2741	2317	1819	1077	591	412.8	302.7	204.8	132.0	120.0	66.0



Kaiying Power Supply & Electrical Equip Co., Ltd Email: sales@longwaybattery.com
 Tel:0595-68782266 Fax:0595-68782222 Website: <http://www.longwaybattery.com>
 Add: Kaiying Industrial Area, Chengxiang Town, Anxi, Quanzhou, Fujian Province, China
 KY-IOP-LW8-200U B0. May 2023

Note: This information usually describes use only and is not intended to make any warranties or promises regarding the battery. Battery specifications and battery design are subject to change without prior notice. Please contact LONGWAY Battery for the latest information.